

EXPRESS MAIL LABEL NO:
EL579666940US

5 METHOD AND APPARATUS FOR PRINTING TRANSPARENT GRAPHICS

Kai Ahrens

BACKGROUND OF THE INVENTION

10

Field of the Invention

The present invention relates generally to a method and an apparatus for printing graphics, and in particular to the printing of documents containing transparent
15 graphics.

Description of Related Art

The most common purpose for which present day personal computers are used is word processing. A word processing application allows the user to create text documents, to edit text documents, and to print text documents on a printer.

Most word processing applications offer the possibility to import graphics into a text document, or
25 to generate graphics in a text document. These graphics may be transparent graphics, which means the graphics may be transparently superimposed on another object of the text document, such as some text or any other graphics object. The most common way to represent such
30 transparency information is the so-called alpha channel, which uses the uppermost eight bits of thirty-two bits for each pixel to represent the transparency information.

In document 100, shown in Figure 1, the graphics objects 110 and 120 are transparent graphics objects. Text object 130 overlaps transparent graphics object 110 and text object 150 overlaps transparent graphics object 120. Text object 140 does not overlap any transparent graphics object.

5

SUMMARY OF THE INVENTION

15

25

35

contained in the transparency list, there is created such a frame defining the bitmap area.

In one embodiment, the frame generated for each object in the transparency list is composed of several subframes, to reduce the area covered by the whole frame. Specifically, the shape of the transparent graphics object together with its overlapping object is approximated by several rectangular subframes to minimize the area covered by the total frame composed of the several subframes.

Hence, in one embodiment, a tool is provided for printing transparent graphics objects contained in a document without the need of converting the whole page where the transparent graphics objects are located into a bitmap. Thereby, the tool saves memory and processing power when printing text documents which contain transparent graphics objects.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an illustration of a text document page containing transparent graphics objects and text that was converted in its entirety to a bitmap for printing in the prior art.

Figure 2 is a block diagram of a computer system used in connection with the present invention.

Figure 3 schematically shows the structure of a text document containing text and transparent graphics objects, and its conversion into a metafile.

Figure 4 is a process flow diagram of a printing method according to one embodiment of the present invention.

Figure 5 shows an example of a text document to be printed using the method of this invention, and the frames used in the method.

In the drawings and the following detailed description, elements with the same reference numeral are the same element. Also, the first digit of a reference

DETAILED DESCRIPTION

Method 230 analyzes document 235 and identifies each region of document 235 that contains a transparent graphics object, a transparent graphics object overlapping a non-transparent object, and no transparent graphics objects. The regions containing transparent graphics objects, or transparent graphics objects overlapping non-transparent objects are converted to bitmaps for printing. The regions of the document, such as text elements, containing no transparent graphics objects are printed without converting these regions into a bitmap. Printing only the transparent graphics objects and any overlapping objects as bitmaps saves both memory usage, and processing power.

- 4 -

In method 230, create metafile operation 410 generates a so-called metafile 236, which is a file containing information about the objects in the document to be printed. More particularly, metafile 236 contains information about which kind of objects - graphics or non-graphics - are to be printed, and where these objects are located on page 300. The generation of such a metafile is often used in a printing process to provide printer 217 with the information necessary for carrying out the printing procedure. Consequently, methods for generating a metafile are known to those of skill in the art.

In operation 420, metafile 236 is examined to determine whether metafile 236 contains transparent graphics objects. A transparent graphics object is a first object, which does not obscure a second object that overlaps the first object. In other words, the second object appears to the user as lying behind the first object that is transparent. The information used to identify the transparent graphics objects in metafile 236 depends upon the particular type of the transparent graphics object. For example, the information may be obtained from the so-called alpha channel for the object, or from the bitmap itself if the object is a bitmap, or perhaps from a recorded action. For example, if the recorded action is DrawTransparentPolygon, the object is a transparent graphics object.

- 5 -

If page 300 did not include any transparent graphics objects, transparency list 237 is empty, and so the processing of this invention is not required.

However, if transparency list 237 contains a reference to one or more transparent graphics objects, list 237 is not empty, e.g., list 237 contains at least one transparent graphics object. Thus, check operation 425 transfers processing to examine for overlap operation 430 that in turn adds to list 237 each object in metafile 236 that overlaps a transparent graphics object.

In overlap check operation 432, the current non-transparent object is checked to determine whether the current non-transparent object overlaps with any of the transparent graphics objects contained in transparency list 237. If an overlap is detected, overlap check operation 432 stops processing and transfers processing to update transparency list operation 440 and otherwise returns to non-transparent object check operation 431 if no overlap was found.

- 6 -

Thus, going through operations 420, 425 and 430 for page 300, transparent graphics objects 310 and 320 are inserted into transparency list 237 in operation 420. Each of remaining objects 330 to 380 is examined as to whether the object overlaps with any one of transparent graphics objects 310 and 320 contained in transparency list 237 in operation 430.

Since object 350 does not overlap with any objects 310 and 320 contained in transparency list 237, object 350 is not inserted therein. However, objects 360 and 370 overlap with transparent graphics object 320. Therefore, objects 360 and 370 are inserted into transparency list 237, thereby completing list 237. Object 380 does not overlap with any of objects 310 and 320 contained in transparency list 237. Therefore, object 380 is not inserted into transparency list 237.

35 In this manner, the undesirable splitting of an overlapping non-transparent object, such as splitting a text element into two elements, one that is printed as a bitmap and one that is printed as characters, can be

avoided since such a split usually leads to unfavorable printing results. This is because when printing characters, the printers today usually use some sophisticated algorithms to improve the resolution and the printing quality. However, for the parts of the text elements printed as a bitmap, the printer could not carry out those algorithms.

Therefore, splitting up a text element overlapping with a transparent graphics object would cause the text element to be printed out in two different printing modes, one part as a bitmap, and the other part as text characters. This problem is avoided by inserting the overlapping non-transparent objects into transparency list 237.

In generate frames operation 450, a frame is generated for each object in transparency list 237. A frame defines an area to be printed as a bitmap. By defining the area to be printed as a bitmap, the frame also defines the area for which there is no need for printing as a bitmap, namely the area lying outside of the frame. In operation 450, for each object contained in transparency list 237, a frame is created defining the bitmap area for that object. Note that a single frame may include one or more objects in list 237.

In one embodiment, the frame generated for each object in transparency list 237 is composed of several subframes to reduce the area covered by the whole frame. A frame defining a bitmap area has to be rectangular. If the object that is printed as a bitmap has a rather complicated shape, generating subframes, which together compose the total frame for this object, can reduce the area covered by the total frame. The shape of the transparent graphics object together with any overlapping objects is approximated by several rectangular subframes to minimize the area covered by the total frame composed of the several subframes.

The operations within operation 450 are more clearly understood by considering another page 500 that includes

05728717-113000

15 In this embodiment to save memory and processing
power, generate frames operation 450 creates a frame for
an object to be printed as a bitmap, such that the area,
which is printed as a bitmap, is made as small as
possible. For this purpose, overlapping compound
20 object 560 containing objects 505, 510, and 520 is not
printed as a bitmap having a single rectangular
frame 531, but rather by a bitmap the shape of which is
formed by three subframes 530, 540, and 550.

- 9 -

prior art, because the complete page is not processed as a bitmap.

Similar processing is carried out for overlapping compound object 570, which also contains a transparent graphics object 515 and two text objects 516 and 517, and where also the overall bitmap for the total bitmap object to be printed is composed of four subframes 571 to 574. Again, the area within subframes 571 to 574 is less than the area within single frame 576. After the frames for the objects in transparency list 237 are created in operation 450, processing transfers to convert to bitmaps operation 455.

To print objects in list 237, the objects in list 237 are converted, in operation 455, into bitmaps as defined by the corresponding frames created in operation 450. The bitmaps and the other portions of document page 500 are printed in print operation 460.

Hence, with method 230 of this invention, bitmap frames 530, 540, 550, 571, 572, 573, and 574 cover less than entire page 500, and therefore whole page 500 is not converted into a bitmap. Rather, some portions of a document page are converted to a bitmap, or bitmaps, while other portions of the page are processed as non-bitmapped data. By reducing the bitmap printing to those objects and text document elements for which it actually makes sense, namely the transparent graphics objects and the overlapping text elements, the printing speed is significantly increased.

In addition by carrying out a bitmap printing only for those parts of a text document for which it actually is necessary, the memory and processing power necessary for the printing are significantly reduced. Those parts of a text document, which contain no elements overlapping with transparent graphics or which contain no transparent graphics themselves, are printed as normal text thereby taking advantage of the sophisticated performance enhancement algorithms implemented in printers for the printing of text characters. The processing and memory

09728717-13000

intensive procedure of bitmap printing is reduced to those areas where such printing is actually necessary to ensure an acceptable level of print quality. Those areas are the areas where transparent graphics objects are
5 located, as well as those areas where text objects are located, which overlap with transparent graphics objects.

Those skilled in the art will readily recognize that the individual operations mentioned before in connection with the procedure of printing according to method 230 of
10 the present invention can be performed by executing computer program instructions on CPU 201 of computer 200. However, in another embodiment, dedicated electronic circuits can be configured such that they perform the individual operations explained before in connection with
15 method 230. In another embodiment, a storage medium has thereon installed computer-executable program code, and execution of the computer-executable program code causes the CPU of a computer to perform the individual operations explained above.

20 In one embodiment, method 230 is executed on a hardware configuration like a personal computer or workstation as illustrated schematically in Figure 2 by computer system 200. However, method 230 may also be executed on a client-server configuration 250 that also
25 is illustrated in Figure 2. The document containing content and template data may be displayed on a display screen of client device 200 while some or all operations of method 230 are carried out on a server computer 280 accessible by the client device 200 over a data
30 network 204, such as the Internet, using a browser application or the like.

Herein, a computer program product comprises a medium configured to store or transport computer readable code for method 230 or in which computer readable code
35 for method 230 is stored. Some examples of computer program products are CD-ROM discs, ROM cards, floppy discs, magnetic tapes, computer hard drives, servers on a

As illustrated in Figure 2, this storage medium may belong to computer system 200 itself. However, the

15 For example, memory 284 could be in a World Wide Web portal, while display unit 216 and processor 201 are in a personal digital assistant (PDA), or a wireless telephone, for example. Conversely, the display unit and at least one of the input devices could be in a client
20 computer, a wireless telephone, or a PDA, while the memory and processor are part of a server computer on a wide area network, a local area network, or the Internet.

35 method 230 as described herein.

Herein, a computer memory refers to a volatile memory, a non-volatile memory, or a combination of the two in any one of these devices. Similarly, a computer

In view of this disclosure, method 230 can be implemented in a wide variety of computer system configurations using an operating system and computer programming language of interest to the user. In addition, method 230 could be stored as different modules in memories of different devices. For example, method 230 could initially be stored in a server computer 280, and then as necessary, a module of method 230 could be transferred to a client device 200 and executed on client device 200. Consequently, part of method 230 would be executed on the server processor 282, and another part of method 230 would be executed on processor 201 of client device 200. Also, Figure 2 shows input devices 215 and 218, but other input devices, such as speech recognition software and/or hardware could be used to input the selections and data for method 230.

In yet another embodiment, method 230 is stored in memory 284 of system 280. Stored method 230 is transferred, over network 204 to memory 211 in system 200. In this embodiment, network interface 283 and I/O interface 202 would include analog modems, digital modems, or a network interface card. If modems are used, network 204 includes a communications network, and method 230 is downloaded via the communications network.

Method 230 may be implemented in a computer program including comprehensive office application STAROFFICE that is available from Sun Microsystems, Inc. of Palo Alto, CA. (STAROFFICE is a trademark of Sun Microsystems.) Such a computer program may be stored on any common data carrier like, for example, a floppy disk or a compact disc (CD), as well as on any common computer system's storage facilities like hard disks. Therefore,

one embodiment of the present invention also relates to a data carrier for storing a computer program for carrying out the inventive method. Another embodiment of the present invention also relates to a method for using a computer system for carrying out method 230. Still another embodiment of the present invention relates to a computer system with a storage medium on which a computer program for carrying out method 230 is stored.

While method 230 hereinbefore has been explained in connection with one embodiment thereof, those skilled in the art will readily recognize that modifications can be made to this embodiment without departing from the spirit and scope of the present invention. It is, for example, readily apparent to those skilled in the art that the present invention can be applied to the printing of any document containing transparent graphics, not only to text documents containing transparent graphics. Furthermore, the overlapping objects, which overlap with the transparent graphics objects, as for example shown in Figures 2, 3, or 5, may not be only text objects but may be any other objects, such as graphics, lines, polygons, any vector objects/vector graphics, etc. Similarly, the non-overlapping objects shown in Figures 2, 3, or 5 may not only be text objects, but any other objects as mentioned before.

In still another embodiment, method 230 is included in a tool for printing documents containing transparent graphics objects and any other objects which either overlap or do not overlap with the transparent graphics objects by dealing with those objects as explained in detail in the foregoing description. Only for exemplary purposes, one embodiment of the invention has been described by referring to text elements as the non-transparent objects, which may overlap or may not overlap with the transparent graphics objects. It is, however, clear to the expert that those overlapping or non-overlapping objects can also take the form of any other non-transparent objects.